

ODIS COLD ROOMS

The ODIS Cold Rooms offer uncompomising quality. Your produce is preserved in its vibrant freshness, extending its journey from farm to table. Our innovation and engineering allow you to choose between a refrigeration system for chilling or freezing.

ASSEMBLE + PLUG

SPECIFICATIONS

Voltage 220-240~, 50/60Hz

Gross Power 1100W
Max Cooling Capacity 1350W
Refrigerant R404A
Refrigerant Charge 1.2kg
Rated Current 6.1A

Configuration Inverter

Temperature Options: Chiller 0°C to 7°C

Freezer -1°C to -18°C

IP Rating IP20

COLD ROOM FEATURES

- ✓ Inverter Refrigeration
- ✓ Rated Compressor Lifetime 12 Years
- ✓ 1EC Condenser Fan + 1 EC Evaporator Fan
- ✓ Four-Way Valve Reverse Cycle Defrost
- ✓ 3m Cable and AU Plug
- √ R404A Refrigerant Pre-Charged by Manufacturer
- ✓ Electronic Expansion Valve & Compatible Superheat Controller
- ✓ Cold Room Panels + Swing Door with Cam Lock Installation
- ✓ Polyurethane PU Sandwich Panel Thickness 100mm
- ✓ Robust 0.526mm Color Steel, Both Sides
- ✓ Density 40kg/m³
- ✓ Total Weight 259kgs
- ✓ Contemporary Off-White Colour
- ✓ 2 Year Warranty

ODIS NAME OF THE PARTY OF THE P
6

COLD ROOM DIMENSIONS	BASE INTERNAL AREA
1HP: 1.8 x 1.2 x 2.2m = 4.75m ³	1.6 x 1.0m = 1.6m ²
1HP: 2.3 x 2.2 x 2.2m = 11.13m ³	2.8 x 2.0m = 4.20m ²